

PPT 8800 Series

With Windows® CE .NET

symbol[®]
The Enterprise Mobility Company™

ENTERPRISE PDA

Small, Rugged and Packed with Power

The PPT 8800 from Symbol Technologies combines superior data capture capability and wireless communications in a rugged handheld computer that is the smallest and lightest device in its class.

The PPT 8800 puts powerful real-time information right in the pocket of the mobile worker and is available with software, peripherals, accessories and services that add compelling value to the operations of companies and enterprises worldwide.

The PPT 8800 is ideal for use in many environments where up-to-date information is needed at the point of activity, including but not limited to:

- ▶ Retail
- ▶ Field Service
- ▶ Public Safety
- ▶ Healthcare
- ▶ Hospitality

Mission-Critical Applications

Designed for mobile workers and managers within the enterprise who require a rugged, high-performance, handheld computer far more durable and reliable than typical consumer devices, the PPT 8800 is powerful enough to execute mission-critical applications, yet small and light enough to be carried in a pocket or on the hip.

The enterprise-friendly PPT 8800 comes packed with features that make it easy for global organizations to manage broad systems deployments.

For more information on the PPT 8800 Series visit www.symbol.com/ppt8800

About Symbol

Symbol Technologies, Inc. (NYSE:SBL), founded in 1975, is a global leader in secure mobile information systems that integrate application-specific handheld computers with wireless networks for data and voice and bar code data capture. Symbol products and services increase productivity and reduce costs for the world's leading retailers, logistics and transportation companies, government agencies, manufacturers and providers of healthcare, hospitality and security.



Features	Benefits
Small and lightweight	Fits in a pocket or on the hip
Large vibrant color display	Easy to see in many environments
Extremely rugged	Endures extreme temperatures and multiple drops to concrete
Sealed to IP54 standards	Protects against water and dust to ensure reliable performance in rough conditions
Laser bar code scanning	Accurate information capture every time
Wireless networking based on the standard IEEE 802.11b (WLAN) or Bluetooth™ (WPAN)	Enables real-time communications and decision making; secure mobile transactions and investment protection
Microsoft® Windows® CE .NET embedded operating system	Easy application development, worldwide support and a large global developer base
Intel® XScale™ architecture	High-speed CPU performance for robust enterprise applications
Rechargeable/replaceable lithium-ion battery	Maximum usage between charges helps to make mobile workers more efficient
Asian language support	Deployable in Japanese, Korean, Chinese Simplified and Chinese Traditional
Multiple keypad options	Flexible functionality and keypad layout that is perfectly suited for targeted applications
Supports AirBEAM®	Wireless device management specifically for enterprises

PPT 8800 with Windows® CE. NET Specification Highlights

Physical Characteristics

Dimensions:	1.3 in. H x 3.1 in. W x 5.7 in. L 33 mm H x 80 mm W x 146 mm L
Weight (including battery):	Batch: 10.1 oz / 286 g WLAN: 10.8 oz / 306 g
Display:	Transflective color TFT-LCD, 65K colors, 240 (W) x 320 (L) (QVGA size)
Touch Panel:	Glass analog resistive touch
Backlight:	LED backlight
Main Battery:	Rechargeable Lithium Ion 1700 mAh (3.7V)
Larger Capacity Battery Option:	Rechargeable Lithium Ion 3400 mAh (3.7V)
Backup Battery:	Ni-MH battery (rechargeable), 15mAh (2.4V) 2 cells

Performance Characteristics

CPU:	Intel Xscale 300MHz processor
Operating Platform:	Microsoft® Windows® CE .NET 4.1
Memory:	32 MB RAM / 32 MB ROM
Embedded options:	IEEE 802.11b Spectrum24 Bluetooth™ 802.15 with encryption support 128 MB Memory card
Communications:	IrDA standard v1.2 (115 kbps) Standard RS-232 (115 kbps)
Audio:	Speaker, microphone
Keypad Options:	Standard version and 15-key with power button version
1D Decode Capability:	UPC/EAN/JAN, Code 39, Code 93, Code 128, Interleaved 2 of 5, Discrete 2 of 5, NW-7, UCC/EAN-128
LED Display:	Upper front center (amber and green)
Scan Triggers:	Left and right trigger buttons

User Environment

Operating Temperature:	14° to 122° F / -10° to +50° C
Storage Temperature:	-13° to 158° F / -25° to 70° C
Environmental Sealing:	IP54 Category II
Humidity:	5% to 90% relative humidity (noncondensing)
Drop Specification:	4 ft./1.2 m drop to concrete
Ambient Light:	Indoor: 450 ft.-candles (4,842 LUX) Outdoor: 8,000 ft.-candles (86,112 LUX)
Electrostatic Discharge (ESD):	+/-15 kVDC (air); +/- 8 kVDC (contact)

Wireless Data Communications

Wireless Local Area Network (WLAN):	Optional IEEE standards-based Spectrum24® 802.11b
Data Rate:	11 Mbps (direct sequence)
Frequency Range:	Country dependent; typically 2.4 to 2.5 GHz
Output Power:	100 mW US; 100 mW international
Spreading Technique:	Direct Sequence
Antenna:	Internal
Wireless Personal Area Network (WPAN):	Bluetooth™ IEEE 802.15

Peripherals and Accessories

Larger Capacity Battery (LCB):	3400 mAh battery with door Kit, Spare 3400 mAh battery
Cradles:	Vehicle cradle with larger capacity battery (LCB) support; single-slot serial charging cradle with spare standard battery charging; single-slot B cradle with LCB support; four-slot Ethernet (connectivity); four-slot serial. Single-slot B and four-slot cradles support terminal with standard battery, terminal with LCB, or terminal with trigger handle attached.
Communication and Cables:	Charging Synchronization/charging cable; worldwide power supplies and cables
4-Slot Universal Battery Charger (UBC):	Simultaneous charge of 1-4 batteries; requires adapters for PPT 8800 1700 mAh/3400 mAh batteries
Vertical-specific attachments:	Magnetic stripe reader, universal cable cup with attachable auto, DEX, printer, and USB cables
Other Accessories:	Holster with easy release clip; holster with velcro belt clasp and belt; slim carrying case; hand strap; neck strap

Regulatory

Electrical Safety:	Certified to UL1950, CSA C22.2 No. 950, EN60950/IEC950
EMI/RFI:	FCC Part 15 Class B, ICES-003 Class B, European Union EMC Directive, Australian SMA
Laser Safety:	CDRH Class II, IEC Class 2
Hazardous Locations:	Certified to UL 913 and CAN/CSA C22.2 no. 157 for use in Class I, Division 2, Groups A, B, C, D



EN410 CE



Specifications are subject to change without notice. All product and company names are trademarks, service marks or registered trademarks of their respective owners. For system, product or services availability and specific information within your country, please contact your local Symbol Technologies office or Business Partner.

NOTICE: Repairs of this product may require the use of Symbol proprietary parts (and/or Symbol proprietary information). Symbol will sell these parts (and provide this proprietary information) only to end-user customers for self-service. It is Symbol's policy not to sell these parts to third-party service providers and not to allow a third-party service provider to act as an ordering or receiving agent for the parts necessary to repair this product.

Corporate Headquarters
Symbol Technologies, Inc.
 One Symbol Plaza
 Holtsville, NY 11742-1300
 TEL: +1.800.722.6234/+1.631.738.2400
 FAX: +1.631.738.5990

For Asia Pacific Area
Symbol Technologies Asia, Inc.
 (Singapore Branch)
 Asia Pacific Division
 230 Victoria Street #05-07/09
 Bugis Junction Office Tower
 Singapore 188024
 TEL: +65.6796.9600
 FAX: +65.6337.6488

For Europe, Middle East and Africa
Symbol Technologies
 EMEA Division
 Symbol Place, Winnersh Triangle
 Berkshire, England RG41 5TP
 TEL: +44.118.9457000
 FAX: +44.118.9457500

For North America, Latin America and Canada
Symbol Technologies
 The Americas
 One Symbol Plaza
 Holtsville, NY 11742-1300
 TEL: +1.800.722.6234/+1.631.738.2400
 FAX: +1.631.738.5990

Symbol Website
 For a complete list of Symbol subsidiaries and business partners worldwide contact us at:
www.symbol.com
 Or contact our pre-sales team at:
www.symbol.com/sales



Part No. PPT8800 Printed in USA 3/04 © Copyright 2004 Symbol Technologies, Inc. All rights reserved. Symbol is an ISO 9001 and ISO 9002 UKAS, RVC, and RAB Registered company, as scope definitions apply.

