SP602

SP602 - PALLET LABELLING (2 stops)

The SP602 is a system for automatic 2-side pallet labelling - requiring two stops of the pallet - when labelled on two adjacent sides.


With the SP602 system we connect you to the world of Zebra® based printers and software. The usage of Zebra Pax III OEM Print Engine ensures you a fast and reliable solution!





The SP602 includes:

- 6" Thermal Transfer Printer
- 2-side pallet applicator
- Cabinet with three doors
- Warning low level labels
- Warning low level ribbon
- Flashlight/beacon
- Check scanner
- · Air regulator, soft start valve
- Harting Industrial Connectors



hand version.

Labelling procedure.

TECHNICAL DATA

Type of applicator: Tamp/Tamp-Blow. The blow can be

switched off

Tamp size: 150 x 210 mm

Print speed: Up to 300 mm/sec

Resolution: 8 or 12 dots/mm 200/300 DPI

Interface: 2 x RS232, 1 x RS485, 1 x USB 2.0

(Ethernet optional)

Cabinet dimensions: 1050 x 680 mm (l x w)

The total height is dependent of label

position and conveyor height.

FAST FACTS

Printer: 6" Thermal Transfer

Application: One label is applied on the front

(or back) and one on the side of a stationary pallet (2 Stops required)

Label size: A5 portrait (150x210 mm)

preferred

Distance: 470 mm from the cabinet to the

applicator pad

Available in both right- and left hand version!

ACCESSORIES

CABINET

- Emergency stop
- · Door interlock switches
- Fan / heating / climate control
- · Electrical height adjustment
- Pneumatic hatch / Sealed doors
- PC-Module

OTHER

- · Ethernet interface
- · Label Check in Applicator Pad

Distributed by:

Manufactured by:

Mectec Elektronik ABAgnesfridsvägen 189, SE-213 75 Malmö, Sweden
P: +46 40 689 25 00 • F: +46 40 689 25 25
info@mectec.se • www.mectec.com