



# Formula 725-E, 725-E/RF

## Hand-Held Laser Terminal

### FEATURES

- Extremely compact and sturdy
- Very light weight (240 g)
- Large data and programme memory capacity and "Overspeed" capability
- High Performance and Long Range models
- 100% compatible with STAR-System™
- Conformance with the European ETSI standard EN 300 220-3
- Excellent price/performance ratio

### APPLICATIONS

- Goods shipping/receiving
- Inventory
- Picking
- Warehouse management
- Shop Floor
- Shelf replenishment and price verification

### GENERAL DESCRIPTION

To improve the efficiency of many crucial activities in your company, such as goods shipping/receiving, inventory and picking, the right choice is to select the **Formula 725-E**, a lightweight, compact-sized and fully programmable hand-held laser terminal available both in batch and wireless configuration.

The **F725-E** batch version offers typical features and functions of high-end products, such as the "overspeed" capability to boost software performance, big RAM memory (up to 2MB) for managing large databases and 512 KB Flash memory to store application programs of large dimensions.

The **F725-E** long-range model can read bar codes located in difficult-to-reach places, even up to 1.5m away, while the reading capacity of the standard model is the best you can desire with the high performance and high visibility laser engine. The wide backlit LCD display, with 4 lines and 16 characters, clearly shows much information while the practical 20-key alphanumeric keyboard allows data to be input very quickly, especially in case the code is unreadable because it is damaged, badly printed or not present at all.

By using the optional EasyGen™ Application Generator or the DS for Formula™ software packages, developers can easily customize applications according to the end user specific needs, while **F725-E/RF** operators can take advantage of the new STAR & Play™ pre-loaded software utility to be immediately operative on the field. The **F725-E/RF** terminal is 100% compatible with Datalogic STAR-System™, the RF narrow band solution for mobile applications. The high capacity Ni-MH long life batteries and the Protecting/Functional case make the **F725-E/RF** the ideal solution for many applications in warehousing/back office environments as well as for intensive use in industrial areas.

If you want to maximise the success of a profitable data capture project and speed up the return on investment, the **Formula 725-E** is the solution you are looking for!



## MODELS AND ACCESSORIES

PRODUCT	DESCRIPTION	ORDER NO.
F725-E/512	F725-E Enhanced Hand-Held Terminal 512KB	941304130
F725-E/2048	F725-E Enhanced Hand-Held Terminal 2048KB	941304140
F725-E/LR/512	F725-E Long Range Enhanced Hand-Held Terminal 512KB	941304150
F725-E/LR/2048	F725-E Long Range Enhanced Hand-Held Terminal 2048KB	941304160
F725-E/RF 512	F725-E/RF Enhanced Radio Hand-Held Terminal 512KB	941354000
F725-E/LR/RF 512	F725-E/LR/RF Long Range Enhanced Radio Hand-Held Terminal 512KB	941354010
<b>ACCESSORIES</b>		
STARGATE™	STARGATE™ RF433MHz Base Station	946104060
F925	F725 Transceiver/Charger - RS232 / RS485	94A15405X
F925 DARK	F725 Transceiver/Charger DARK - RS232 / RS485	94A15107X
F925/4	F725 Transceiver/Charger - 4 slots - RS232 / RS485	94A15407X
FCB232 D 9 F Transceiver	RS232 serial cable for PC (9-pin type D Female) 2 m	94A054000
F902	T-Box	94ACC4020
NCK RS485	Network/PC connection kit	94ACC400X
FCB485	SYS RS485 serial connection cable for SYSNET 2m	94A054020
FCB EAV	Eavesdrop cable kit 2+2 m	94A054030
FBK725	Battery Kit Ni-CD F725	94ACC4200
FBS725	Battery Kit Ni-CD F725 (5PCS)	94ACC4210
FBK725-E	Battery Kit Ni-MH F725-E	94ACC1261
FBS725-E	Battery Kit Ni-MH F725-E (5PCS)	94ACC1262
FCT725	Functional Case F725 with swivel	94ACC1267
DS FOR FORMULA™	Development system for Formula Basic Line	94A104860
CA51	Compiler 8051 Compiler kit V6 for F6xx and F7xx	94A104890
EASYGEN™	Easy application generator package for Formula batch terminals: F660, F725, F732, F734	94A104850
ForWin™ D5	Screen Generator for Formula Basic Line RF terminals (5 Licences)	94A101011
ForWin™ R5	Runtime ActiveX 5 Licences	94A101012
ForWin™ R10	Runtime ActiveX 10 Licences	94A101013
ForWin™ RUL	Runtime ActiveX Unlimited Licences	94A101014
ForWin™ KIT	Start-up Kit (Screen Generator + Runtime ActiveX 5 Licences)	94A101015
UTILITY TOOLS FULL PACK ADV. ED. F725	Software package for Windows 95, 98, NT	94A104160

\*X=1 - power supply for USA; 2 - power supply for Europe; 4 - power supply for UK; 5 - power supply for Australia

## SPECIFICATIONS

<b>OPERATIVE SYSTEM</b>	Datalogic proprietary	<b>RADIO COMMUNICATION</b>	
<b>PROCESSOR</b>	8 bit CMOS	<b>RADIO FREQUENCY</b>	433.92 MHz
<b>PROGRAMME MEMORY</b>	512 KB Flash dedicated to the application program	<b>RADIO POWER OUTPUT</b>	<10 mW
<b>DATA MEMORY</b>	512 KB, 2048 KB RAM for data	<b>RADIO RANGE*</b>	50 m (164 ft)
<b>DISPLAY</b>	Graphic high-contrast LCD with backlight	<b>DATA TRANSFER RATE</b>	up to 19,200 baud
<b>SCREEN FORMAT</b>	4 lines x 16 characters	<b>CONFORMITY</b>	European ETSI standard EN 300 220-3
<b>KEYBOARD</b>	Alphanumeric with 20 silicon rubber keys	<b>DIMENSIONS (LxWxH)</b>	110 x 56 x 147 mm (4.3 x 2.2 x 5.8 in)
<b>SIGNAL TO OPERATOR</b>	Bicolour LED; Piezoelectric buzzer; programmable frequency and duration	<b>WEIGHT</b>	
<b>CLOCK/CALENDAR</b>	Quartz controlled RTC; programmable date and time	Batch models	240 g (8.5 oz)
<b>SCANNING RATE</b>	36 scans/sec	RF models	255 g (9.01 oz)
<b>MINIMUM RESOLUTION</b>	0.127 mm (5 mils)	<b>OPERATING TEMP.</b>	0 to 50 °C (32 to 122 °F)
<b>DEPTH OF FIELD (depending on bar code thickness)</b>	standard model 3 to 70 cm (1.2 to 27.6 in) Long range model 10 to 150 cm (3.9 to 59.1 in)	<b>DROP RESISTANCE</b>	Resists several drops onto concrete
<b>READING ANGLES</b>	±65° skew; ±55° pitch	<b>ENVIRONMENTAL PROTECTION</b>	Industrial, protected against dust and water
<b>BAR CODES</b>	EAN 8, EAN 13, UPC/A-E, 2/5 family, Code 128, Code 93, Code 2/7, Code 3/5, 3/9 family, MSI, DELTA A IBM		
<b>LASER CLASSIFICATION</b>	VLD - Class II		
<b>POWER SOURCE</b>			
Batch models	250 mA/h Ni-CD rechargeable batteries		
RF models	600 mA/h Ni-MH rechargeable batteries		
<b>AUTONOMY</b>	24 h, with reading every 45"		
<b>BATTERY CHARGING</b>	Via Formula 925 single slot Transceiver/Charger or Formula 925/4 multiple slot Transceiver/Charger		
<b>SERIAL COMMUNICATION</b>	Infrared (via optocoupler) between F725-E and F925 or F925/4		
	RS232 or RS485 between F925 or F925/4 and PC or Host		
	Transmission speed: up to 57,600 baud		

\* The radio range depends on the environment characteristics

## ACCESSORIES



STARGATE™ RF Base Station



DS for Formula™ Package

**DATALOGIC**  
code evolution



Product and company names and logos referenced may be either trademarks or registered trademarks of their respective companies.

We reserve the right to make modifications and improvements

### Datalogic S.p.A. Italy

Corporate Headquarters  
Tel. +39 051/3147011  
Fax +39 051/726562  
info@datalogic.it

Sales Italy  
Tel. +39 051/3147011  
Fax +39 051/3147170  
venditeitalia@datalogic.it

Sales International  
(Central and South America,  
Far East, Middle East - Africa)  
Tel. +39 041/5986511  
Fax +39 041/5986550  
sales-intl@datalogic.it

### Australia

Datalogic PTY LTD.  
Tel. +61 3/95589299  
Fax +61 3/95589233  
sales@datalogic.com.au

### Germany

Datalogic GmbH  
Tel. +49 7026/6080  
Fax +49 7026/5746  
info@datalogic.de

### Sweden

Datalogic AB  
Tel. +46 40/385000  
Fax +46 40/385001  
info@datalogic.se

### Austria

Datalogic Handelsges. mbH  
Tel. +43 2236/258820  
Fax +43 2236/258825  
office@datalogic.co.at

### Japan

Izumid Datalogic Co., Ltd.  
Tel. +81 78/3033400  
Fax +81 78/3033402  
idlmarke@izumi-datalogic.co.jp

### United Kingdom

Datalogic UK Ltd.  
Tel. +44 1582/464900  
Fax +44 1582/464999  
enquiries@datalogic.demon.co.uk

### Denmark

Datalogic A/S  
Tel. +45 70/239970  
Fax +45 70/239972  
info@datalogic.se

### Netherlands

Datalogic Optic Electronics BV  
Tel. +31 346/572888  
Fax +31 346/568736  
info@datalogic.nl

### U.S.A.

Datalogic Inc.  
Tel. +1 859/6897000  
Fax +1 859/3344970  
info@datalogic.com

### France

Datalogic France S.A.  
Tel. +33 1/60921111  
Fax +33 1/60921340  
info@datalogic.fr

### Spain

Datalogic Iberia  
Tel. +34 91/3837755  
Fax +34 91/3837962  
dliberia@datalogic.it

### Datalogic Quality Partner

